



HIRSCHMANN

A **BELDEN** BRAND

Wireless Sensors

Proven Sensor Technology

Controls
Consoles
SLIs
Sensors
Service



Console Options:



iSCOUT PRS40

Indicator system for mobile cranes



iFLEX TRS05

Compatible with most Hirschmann/PAT systems on hydraulic or lattice cranes



iSCOUT PRS80

Wireless multi-sensor indicator for mobile cranes



iVISOR mentor

Console with integrated controls



HIRSCHMANN

A BELDEN BRAND



Wireless Wind Speed Sensor

- Three cup wind speed sensor
- Designed for operation in adverse environments
- Quick pivot pedestal mount for quick and easy installation
- Accuracy +/- 2.5 mph



Wireless Angle Sensor

- Accuracy of +/- 1.0 degree
- Compact and durable design
- Fully electronic
- Wide temperature range



Wireless Anti-Two Block Switch

- Uses proven PAT A2B Switch
- Designed to be installed quickly and easily
- Moves easily between mainboom and jib
- Rugged design (sealed and potted)
- Mounts to existing A2B hole pattern



Wireless Load Cells

- Load measured to an accuracy of +1%
- Installs easily on headache ball or hook block (dead end)
- Capacity: 15,000 lbs. and 45,000 lbs.
- Durable stainless steel design

Other products from Hirschmann:



iVISOR maestro

Upgrade existing PAT/Hirschmann LMI's to the latest technology



iVISOR MK4E/2

Load Moment Indicator (LMI) for mobile cranes

Specifications are subject to change without notice.



Cranes & Equipment Specialists of Chicago

10900 S. 85th Ave., Palos Hills, IL 60465-2379
Phone: (708) 636-6010 • Fax: (708) 974-2528
Email: sales@cescrane.com

©Copyright 2012, Belden Inc.

www.cescrane.com

